

The 900E Series exit features an architectural, slim design to fit into any environment. Attractive and functional, the 900E Series is completely self-contained and utilizes reliable, energy efficient LED illumination.

FEATURES

- Attractive specification-grade aluminum design
- High clarity acrylic panels
- Ceiling recessed, wall recessed, surface ceiling, wall or end mount
- Custom legends available
- 120/277VAC dual primary, 50/60Hz input
- Low voltage disconnect eliminates deep discharge
- Brown-out, short circuit and voltage surge protection
- Maintenance-free NiCad (NC), NiMH (G2) and SLA (WB) batteries
- Optional Guardian Self-Test/ Self-Diagnostics (A1/G2) available
- Constant, uniform illumination by long-life, high intensity, red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke
- Field selectable directional chevrons included for all configurations
- Standard finishes: Black, White or Brushed Aluminum
- Assembled in U.S.A.

WARRANTY

Any component that fails due to manufacturers defect is guaranteed for 25 years with a separate 5 year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Extronix warranty document for detailed information.



Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



Custom legends available



ORDERING INFORMATION Example: 902E-U-WB-RM-BA-G2

Series	Mounting	Power Source	Panel Color	Finish	Options (Factory Installed)
902E = Single Face	R = Recessed	LB = AC Only	RC = Red Letters/Clear Panel	WH = White	A1 ^{4,5} = Fire Alarm Interface w/Flasher
903E ¹ = Dbl. Face	WR ² = Wall Recessed	WB = With Battery	RW = Red Letters/White Panel	BL = Black	DR = Damp Location Rated
	U = Universal Surface	NC = NiCad	RM = Red Letters/Mirror Panel	BA = Brushed Alum.	G2 ^{4,5} = Self-Test/Self-Diagnostics
		2CI1 ³ = 2 Circuit Input 120/120V	GC = Green Letters/Clear Panel		G2-220V ^{6,7} = Self-Testing/Self-Diagnostics
		2CI7 ³ = 2 Circuit Input 277/277V	GW = Green Letters/White Panel		G2-230V ^{6,8} = Self-Testing/Self-Diagnostics
		2CI17 ³ = 2 Circuit Input 120/277V	GM = Green Letters/Mirror Panel		G2-240V ^{6,9} = Self-Testing/Self-Diagnostics

Notes

- ¹ Double face available with white or mirror panel only
- ² Single face, clear panels only (RC or GC)
- ³ 2CI not available with G2 option
- ⁴ A1 and G2 options can not be combined
- ⁵ Not available with NiCad battery option, NiMH only
- ⁶ Available with battery units only, cannot be combined with any other options
- ⁷ 220V version
- ⁸ 230V version
- ⁹ 240V version

¹⁰ Consult factory for alternate legends and custom configurations

¹¹ Order as separate line item, surface mount only

Accessories¹¹ (Field Installed)

- ER1-KIT = 1' Pendant Mount Kit
- ER2-KIT = 2' Pendant Mount Kit

