

ULTRA 75' SERIES UL924 PHOTOLUMINESCENT EXIT SIGN



**Ultra Durable
Ultra Eco Friendly
Ultra Economical
Ultra Light Weight
Ultra Easy to Install
Ultra Easy to Wash
Ultra Thin**

NEW!



Lights off

Viewing distance of 75'

NO FRAME NEEDED

15 Year Limited Warranty



Surface mount signs are provided with two pre-drilled holes for fast and easy installation.

Universal Kit

Includes everything you need!

- 1 Exit Sign, 9.5"Hx16"Lx1/8"W
- Pair of Peel & Stick Directional Chevrons
- Mounting Bracket, 4"x2.5" and Hardware

Available Colors



- Non-electric
- Non-radioactive
- Non-hazardous
- No expiration date
- Energy efficient
- LEED points qualified
- Zero annual operating expense
- No batteries
- No bulbs
- Low maintenance
- 100% reliable
- High or low level
- Simple installation
- 25+ year life expectancy



Designed for maximum durability, the BPL Ultra 75 Series Photoluminescent Exit Sign is constructed using a poly metal material. Ideal for high and low level applications. Easy peel and stick directional chevrons. UL 924 Listed with four external charging light sources: fluorescent, metal halide, LED, and mercury vapor.

Overall Size: 16"W x 9"H x .1/8" Depth
 Letter Size: 1" Stroke, 7.5" Height
 Weight: 1 lbs
 Construction: Poly metal material with photoluminescent lettering
 Illumination: Strontium Oxide Aluminate Photoluminescent Pigment

Face Plate Colors: Black, Green, Red, Silver and White
 Letter Color: Photoluminescent, Green Illuminating
 Directional: Pair of Peel & Stick Directional Photoluminescent Chevrons
 Initial Activation: Based on UL 924 Standards, requires minimum 5 foot-candles (54 lux) of unfiltered fluorescent, metal halide, LED or mercury vapor lighting for 60 minutes.

Installation: Install photoluminescent exit signs only in locations where an external illumination source is present, is deemed reliable, and is supplied by a circuit not controlled by automatic timers or sensors and where controls are accessible only to authorized personnel. This reliable external illumination source is to be energized at all times during building occupancy.

Viewing Distance: 75 Feet - Sign will remain visible and legible in total darkness to observers standing 75 feet away from the sign for at least 90 minutes after all light has been extinguished.



Life Expectancy: 25+ years
 Applications: High and low level, indoor use only
 Approvals: UL 924 Listed, Meets NFPA 101 Life Safety Code, NFPA 5000, JCAHO & OSHA, ICC, - IBC, ICBO - UBC, BOCA - NBC, SBCCI - SBC, 1/UFC, CA Bldg. Code, ASTM 2072 and CSFM Listed

Product Care: Periodically clean the sign face with a damp cloth, and conduct periodic inspections to ensure the sign is clear and visible.

Warranty: 15 year limited warranty from the date of shipment against defects in workmanship and materials to the original customer

Mounting Options

Surface • Ceiling • Flag • T-Bar



Description

Description	Item No.'s
black, wall mount exit sign	UT75WB
black, single-sided sign w/bracket	UT75SB
black, double-sided sign w/bracket	UT75DB
black, single-sided sign w/T-bar bracket	UT75STB
black, double-sided sign w/T-bar bracket	UT75DTB
silver, wall mount exit sign	UT75WS
silver, single-sided sign w/bracket	UT75SS
silver, double-sided sign w/bracket	UT75DS
silver, single-sided sign w/T-bar bracket	UT75STS
silver, double-sided sign w/T-bar bracket	UT75DTS
red, wall mount exit sign	UT75WR
red, single-sided sign w/bracket	UT75SR
red, double-sided sign w/bracket	UT75DR
red, single-sided sign w/T-bar bracket	UT75STR
red, double-sided sign w/T-bar bracket	UT75DTR
green, wall mount exit sign	UT75WG
green, single-sided sign w/bracket	UT75SG
green, double-sided sign w/bracket	UT75DG
green, single-sided sign w/T-bar bracket	UT75STG
green, double-sided sign w/T-bar bracket	UT75DTG
white, wall mount exit sign	UT75WW
white, single-sided sign w/bracket	UT75SW
white, double-sided sign w/bracket	UT75DW
white, single-sided sign w/T-bar bracket	UT75STW
white, double-sided sign w/T-bar bracket	UT75DTW

